




### Model Number

NEB3-8GM45-E

### Features

- Comfort series
- 3 mm quasi-embeddable
- increased operating distance

### Connection




### Accessories

#### BF 8

Mounting flange

## Dimensions



## Technical Data

### General specifications

Switching element function	NPN Make function
Rated operating distance	$s_n$ 3 mm
Installation	quasi embedd.
Output polarity	DC
Assured operating distance	$s_a$ 0 ... 2.43 mm
Reduction factor $r_{Al}$	0.36
Reduction factor $r_{Cu}$	0.27
Reduction factor $r_{V2A}$	0.77

### Nominal ratings

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 1000 Hz
Hysteresis	$H$	typ. 5%
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 2$ V
Operating current	$I_L$	0 ... 200 mA
Off-state current	$I_r$	0 ... 0.1 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$	$\leq 10$ mA
Indication of the switching state		LED, yellow

### Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

### Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

### Mechanical specifications

Connection type	2 m, PUR cable
Core cross-section	0.14 mm <sup>2</sup>
Housing material	brass, chromium plated
Sensing face	PBT
Protection degree	IP67