


**Model Number**

NRB5-18GM50-E2-C-V1

Features

- Reduction factor = 1
- 5 mm embeddable
- Resistant to welding

Connection**Accessories****BF 18**

Mounting flange

V1-G

Non pre-wired cable socket

V1-W

Non pre-wired cable socket

V1-G-2M-PUR


Cable connector

V1-W-2M-PUR

Cable connector

EXG-18

Mounting aid

Dimensions**Technical Data****General specifications**

Switching element function	PNP Make function
Rated operating distance	s_n 5 mm
Installation	embeddable
Output polarity	DC
Assured operating distance	s_a 0 ... 4.05 mm
Reduction factor r_{Al}	1
Reduction factor r_{Cu}	1
Reduction factor r_{V2A}	1
Reduction factor r_{St37}	1

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 350 Hz
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Rated insulation voltage	U_{BIS}	60 V
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 15 mA
Constant magnetic field	B	200 mT
Alternating magnetic field	B	200 mT
Indication of the switching state		Multihole-LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V1-connector
Housing material	brass, teflon coated
Sensing face	PPS
Protection degree	IP67
Protection class	II

Approvals and certificates

UL approval	cULus Listed, General Purpose
-------------	-------------------------------