




CE

**Model Number**

NRN15-30GM50-E2-C-V1

**Features**

- Reduction factor = 1
- 15 mm not embeddable
- Resistant to welding

**Connection****Accessories****BF 30**

Mounting flange

**V1-G**


Non pre-wired cable socket

**V1-G-2M-PUR**

Cable connector

**EXG-30**

Mounting aid

**Dimensions****Technical Data****General specifications**

Switching element function	PNP Make function
Rated operating distance	$s_n$ 15 mm
Installation	not embeddable
Output polarity	DC
Assured operating distance	$s_a$ 0 ... 12.15 mm
Reduction factor $r_{Al}$	1
Reduction factor $r_{Cu}$	1
Reduction factor $r_{V2A}$	1

**Nominal ratings**

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 20 Hz
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 3$ V
Operating current	$I_L$	0 ... 200 mA
Off-state current	$I_r$	0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$	$\leq 15$ mA
Constant magnetic field	$B$	100 mT
Alternating magnetic field	$B$	100 mT
Indication of the switching state		Multihole-LED, yellow

**Standard conformity**

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

**Mechanical specifications**

Connection type	V1-connector
Housing material	brass, teflon coated
Sensing face	PPS
Protection degree	IP67